

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

MASTER SPRAY CLEAR COAT



PRODUCT DESCRIPTION

Fast drying, one component clear coat characterized by high gloss and very good adhesion to various kind of surfaces (metal, aluminium, wood, glass, stone and various types of plastic). Product has anti-corrosive properties, provides long term protection against scratches and bumps, it's resistant to chemical substances action and weather conditions.

PHYSICAL AND CHEMICAL PROPERTIES

- Color: transparent
- Glass grade: high gloss
- Capacity: 500 ml.
- Efficiency: 1,5 – 2 m²
- Base: acrylic resin
- Density: 0,755 g/cm³ (in temp. 20⁰C)
- Temperature resistance: to 110⁰C

Drying time (in temp. 20⁰C) :

- Dust dry: after approx. 5 – 10 minutes
- Tack free: after approx. 10 - 20 minutes
- Completely dry: after approx. 2 hours

Note: Drying time depends on air temperature, humidity and thickness of the layer.

VOLATILE COMPONENTS CONTENT

VOC = 666,3 [g/l]

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.

USAGE

- The best results are achieved applying at room temperature. The ambient temperature and the temperature of the product should be the same.
- Surface should be dry, degreased, clean from dirt and rust and gently sanded.
- Shake before using for 2 minutes and try it on cardboard.
- During lacquering hold aerosol in 25÷30 cm distance from the surface.
- Apply one or two layers, depending on the needs.
- **Clean the spray nozzle after use!** – Hold the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.

STORAGE

Store the product in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

WARRANTY PERIOD

5 years from production date.